

You are here: [OBO Construct TBS](#) » [Project categories](#) » [Typ1: MCD50-B](#) » [MCD 50-B 3+1](#)

## MCD 50-B 3+1



| Type         | Weight<br>kg/100 pcs. | Art. no. |
|--------------|-----------------------|----------|
| MCD 50-B 3+1 | 168                   | 5096879  |

Coordinated lightning cont. set for TT and TNS networks

## Technical data

|                                            |                |
|--------------------------------------------|----------------|
| SPD to EN 61643-11                         | Type 1+2       |
| SPD to IEC 61643-11                        | Class I+II     |
| Total discharge current (10/350) (kA)      | 125            |
| Protection rating                          | IP20           |
| Max. continuous operating voltage (V)      | 255            |
| Version                                    | 3 + NPE        |
| Lightning protection zone LPZ              | 0→2            |
| Impulse discharge current (10/350) (kA)    | 50             |
| Temperature range (°C)                     | -40 - +85      |
| Installation type                          | Hat rail 35 mm |
| Division unit TE (17.5 mm)                 | 8              |
| Connection cross-section, flexible (mm²)   | 10 - 25        |
| Connection cross-section, multi-wire (mm²) | 10 - 35        |
| Connection cross-section rigid (mm²)       | 10 - 50        |

## Tender text