

Surge protection

You are here: OBO Construct TBS » Project categories » Typ1: V50 » V50-3-280

V50-3-280



Type	Weight kg/ 100 pcs.	Art. no.
V50-3-280	46.5	5093511

CombiController V50 3-pole

[HOMEPAGE](#)
[LOGIN](#)
[PROJECT PLANNING](#)
[PRODUCT CATEGORIES](#)
[MATERIAL LIST](#)
[CONTACT](#)
[IMPRINT](#)

Technical data

SPD according to EN 61643-11	Type 1+2
SPD according to IEC 61643-1	class I+II
Pulse current (10/350) [total] [kA]	37.5
Maximum discharge current I_{max} [kA]	50
Response time t_A [ns]	25
Protection class	IP20

Tender text

CombiController V50

Lightning current combination arrester, type 2

- For the equipotential bonding of lightning current to VDE 0185-305 (IEC 62305)
- Lightning current discharge capacity of 12.5 kA (10/350) per pin and up to 50 kA (10/350) in total
- Modular, plug-in arrester with dynamic cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Halogen-free plastic (UL 94 V-0)
- The FS variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.

Fabrikat: OBO BETTERMANN

Type: V50-3-280

Item No.: 5093511

Einheit:

THINK CONNECTED.

1.1.2

© 2016 OBO BETTERMANN GmbH & Co. KG | Imprint | Exclusion of liability | Data protection | Copy right | Terms of use